


REMARKS

If there are any questions regarding this amendment or the application in general, a telephone call to the undersigned would be appreciated since this should expedite the prosecution of the application for all concerned.

If necessary to effect a timely response, this paper should be considered as a petition for an Extension of Time sufficient to effect a timely response, and please charge any deficiency in fees or credit any overpayments to Deposit Account No. 05-1323 (Docket #951/49898).

Respectfully submitted,



Donald D. Evenson  
Registration No. 26,160

DDE:mkh  
CROWELL & MORING, LLP  
P.O. Box 14300  
Washington, DC 20044-4300  
Telephone No.: (202) 628-8800  
Facsimile No.: (202) 628-8844

09858522 110501

Marked-Up Version of PCT EP99/08989  
Filed November 22, 1999

MOTOR VEHICLE AUDIO SYSTEM

BACKGROUND AND SUMMARY OF THE INVENTION

The invention relates to a motor vehicle audio system [having the characteristics of the preamble of Claim 1] comprising an audio signal receiver, at least one amplifier connected thereto by way of an optical waveguide, and a loudspeaker.

A system of this type is known from European Patent Document EP 0 027 043 B (corresponding U.S. Patent No. 4,282,605). Such an audio system is operated by means of an operating voltage which is equal to the normal onboard power supply voltage of preferably 12 volt. In the case of loudspeakers with a resistance of 8  $\Omega$ , particularly in the case of powerful amplifiers, a distortion factor occurs which is also clearly noticeable acoustically and which impairs the listening enjoyment. If, on the other hand, a higher operating voltage is to be used for the amplifiers in order to avoid the harmonic distortion, the interferences, which necessarily occur in the onboard power supply and which also occur on the supply lines of the amplifiers, result in clearly audible clicks and plops.

It is an object of the invention to provide an audio system of the initially mentioned type which permits an undisturbed listening enjoyment.

The invention achieves this object by [means of the characteristics of Claim 1] providing an audio system of the type referred to above, wherein a separate amplifier is supplied with a significantly higher operating voltage than the at least one amplifier for other audio frequencies.

The invention provides a separation of the audio signals of the bass range and a separate amplification therefor. The high operating voltage is used only for supplying the separate amplifier. In addition, the use of two independent amplifiers can also be provided for the medium/high frequency range.

The amplifier of the bass range receives a supply voltage of preferably 42 volt, while the medium/high frequency range is supplied with, for example, 12 volt.

Occurring electric interferences do not affect the bass range because they have significantly higher frequencies. The use of a supply voltage of 42 V therefore results in a high power yield in the low-bass range while simultaneously acoustic interferences cannot be perceived. In contrast, such a high power yield is not required for the medium/high frequency range.

008852 4054

The use of amplifiers with 12V permits a sufficient power yield. The power required for the medium/high frequency range can and will clearly be lower than for the bass range.

The invention will be further explained by means of the drawing.

BRIEF DESCRIPTION OF THE DRAWING

The single drawing figure is a schematic top view of an automobile with an audio system constructed according to a preferred embodiment of the invention.

DETAILED DESCRIPTION OF THE DRAWING

The only figure is a top view of the systematic construction of an audio system according to the invention. An audio signal receiver (radio) 1 is connected with amplifiers 5 and 6 by way of optical waveguides 2 to 4. At least one of the optical waveguides 2 to 4 is a component of a (ring) bus system.

At the beginning and the end of each of the optical waveguides, an electro-optical or opto-electrical transducer is situated which transforms the incoming electrical or optical signals into corresponding optical or electrical signals.

FOUO F. 2253860

Subwoofers 7 and 8 for the playback of deep audio frequencies are connected to the output side of the amplifier 5, and medium/high frequency speakers 9 and 10 for the playback of the correspondingly remaining audio frequencies are connected to the output side of the amplifier 6.

According to the invention, the amplifier 5 is supplied with an operating voltage of 42V and the amplifier 6 is supplied with an operating voltage of 12V.

As a result of the galvanic separation of the radio 1 and the amplifiers 5 and 6, electrical interferences, which occur mainly in but also outside the vehicle, are not transmitted to the amplifiers 5 and 6. By means of the amplifier 5, a high power yield can be obtained. Since, as a result, only deep frequencies are amplified and played back by way of the loudspeakers 7 and 8, occurring high-frequency interferences are not noticeable acoustically.

The medium/high frequency speakers 9 and 10 are supplied with a lower operating voltage of 12V. The thus achievable power yield of, for example, 20W, is sufficient also in cases in which the subwoofers 7 and 8 are acted upon by a high power of, for example, 100W. As a result of the lower power requirement, the distortion factor can therefore be minimized.